

Setting the informed consent using a survey

Creating the survey

Create a question with the code name 'informedconsent'. You can choose many types of questions types. The answers to the questions are translated to a consent using this algorithm that checks the answer against the consents stored in Setup ⇒ Codes ⇒ Consents.

- If the answer is the same as a consent “Description”, that consent is used.
- If the answer is the same as the start of a consent “Description”, that consent is used. This is in case you have e.g. only 5 characters to enter the answer.
- If the answer is a “value” the the first consent by “Order” with the “Consent code” “consent given” will be used. **Warning:** examples of valid values are:
 - “Y”
 - “N”
 - “Unknown”
 - “X”
 - 1
 - -1
- If the answer is not a “value” the the first consent by “Order” with the “Consent code” “do not use” will be used. Not-values are:
 - An empty string
 - 0

Using the survey

- Activate the survey in LimeSurvey
- Synchronise the LimeSurvey source in GemsTracker (Track Builder ⇒ Survey Sources → Synchronize surveys)
- Activate the survey in GemsTracker (Track Builder ⇒ Surveys ⇒ Edit)
- Check “Active in...” and select a group (usually Respondents)
- Select the “After completion” event “Use the 'informedconsent' answer to set the informed consent. (Gems)”.
- Save the survey.

If you then use and answer the survey the informed consent will be set tot the 'informedconsent' field as long as it is not empty.

From:
<https://gemstracker.org/wiki/> - GemsTracker

Permanent link:
https://gemstracker.org/wiki/doku.php?id=userzone:userdoc:setting_the_informed_consent_using_a_survey

Last update: 2020/03/12 11:06

